Hios CLT Series Power Supplies

Product Images



Description

The HIOS CLT Series Power Supplies are suitable for use with HIOS torque screwdrivers. Featuring a safe and quiet rotation, the CLT-45 and CLT-60 Power Supplies can power a single tool at a time, whilst the CLT-100 can power two tools at once

- Current is taken directly from the AC outlet, converts it to low voltage output and then supplies it to the screwdriver
- Plug shape: A-1 / A-2 / A-3 / C / BF / S
- CLT45:
- Primary side input power supply: AC100-240V (47-63Hz)
- Secondary output voltage: HI (2): DC30V, LOW (1): DC20V 2-stage switching type
- Attachment: One power cord 1.8m, one 2P conversion plug (attached only to 100V), one mounting bracket, one mounting screw
- CLT60:
- Primary side input power supply: AC100-240V (47-63Hz)
- Secondary output voltage: HI (2): DC30V, LOW (1): DC20V 2-stage switching type
- Attachment: One power cord 1.8m, one 2P conversion plug (attached only to 100V), two mounting brackets, 4 mounting screws



Riverside Commercial Estate, T: +353 91 745 150 Galway, H91 X4DK, Ireland.

E: sales@safetydirect.ie W: www.safetydirect.ie

- CLT100:
- Connection for 2 tools
- Primary side input power supply: AC100V (50 / 60Hz)
- Secondary output voltage: HI (2): Approx. DC30V, LOW (1): Approx. DC20V 2-stage switching
- Attachment: One power cord 1.8m (with ground wire)



