

Miller Turbolite Edge 2M Lifeline with Automatic Twistlock and GO60 Scaff Hook

Product Images



Description

The Miller Turbolite Edge 2M Lifeline is a self-retracting lifeline with reinforced webbing that is ideal for use in several environments. Edge-tested to 140kg, the 2M Lifeline can be used horizontally without any restrictions, and has two swivels on the anchorage connection and housing to avoid twisting of the webbing

- Lightweight yet highly durable and secure
- Suitable for use in many environments, including those that require the possibility to connect at foot level when working on the edge
- Adapted to all fall factors: FFO, FFI, FF2
- Can be used horizontally without restriction, with reinforced webbing
- 2 swivels (on anchorage connection karabiner and housing) to eliminate twist effect of webbing and improves the ability of the webbing to retract
- Harness connection: aluminium twist-lock karabiner, opening 18mm
- Anchorage connection: connector 1033463 - aluminium scaff hook GO60 with integrated swivel, opening 60mm
- Anchorage connection is 'self-locking'; turn and push down to open
- Can be inspected easily due to integrated fall indicator
- Max. length 2m
- Max. rated load: 140kg
- Breaking strength: 1700 DaN

- EN 360:2002, VC11.062 (140kg), VC11.085 (FF2), VC11.060 (edge-tested)



Riverside Commercial Estate,
Galway, H91 X4DK,
Ireland.

T: +353 91 745 150
E: sales@safetydirect.ie
W: www.safetydirect.ie