

HazMat Socks #YSO430 - 3" x 4', 30 socks/package



When hazardous liquids spill, use HazMat Sorbents for quick, efficient response. These 100% polypropylene Socks contain and soak up acids, bases and unknown fluids fast.

- Contain and absorb hazardous or unknown spills
- 100% polypropylene filler (most chemically compatible)
- Fits snugly around the bases of leaky drums and containers
- Color-coded cautionary yellow for fast identification
- NOTE: Ideal for use with battery acid but not compatible with higher concentrations of sulfuric acid

YSO430 Specifications

Dimensions:	ext. dia. 3" x 4' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	30 socks per package
Color:	Yellow
Composition:	100% Polypropylene
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 106.6 oz. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 121.9cm L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 3.2 L per sock
Weight:	13.6 kg







YSO430 Technical Information

Warnings & Restrictions:

Color Variance Notice Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)





Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)



HazMat Socks #YSO815 - 3" x 8', 15 socks/package



Keep fluids from spreading to larger areas.

- Contain and absorb hazardous or unknown spills
- 100% polypropylene filler (most chemically compatible)
- · Fits snugly around the bases of leaky drums and containers
- Color-coded cautionary yellow for fast identification
- Note: Ideal for use with battery acid but not compatible with higher concentrations of sulfuric acid

YSO815 Specifications

Dimensions:	ext. dia. 3" x 8' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	15 socks per package
Color:	Yellow Speckled Filler/Yellow Sleeve
Composition:	100% Polypropylene
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 1.7 gal. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 2.4m L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 6.4 L per sock
Weight:	13.6 kg







YSO815 Technical Information

Warnings & Restrictions:

Color Variance Notice Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)





Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)



HazMat Socks #YSO1210 - 3" x 12', 10 socks/package



Keep fluids from spreading to larger areas.

- Contain and absorb hazardous or unknown spills
- 100% polypropylene filler (most chemically compatible)
- · Fits snugly around the bases of leaky drums and containers
- Color-coded cautionary yellow for fast identification
- Note: Ideal for use with battery acid but not compatible with higher concentrations of sulfuric acid

YSO1210 Specifications

Dimensions:	ext. dia. 3" x 12' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	10 socks per package
Color:	Yellow Speckled Filler/Yellow Sleeve
Composition:	100% Polypropylene
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 2.5 gal. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 3.7m L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 9.5 L per sock
Weight:	13.6 kg







YSO1210 Technical Information

Warnings & Restrictions:

Color Variance Notice Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)









Oil-Only Poly Blend Socks #WSO430 - 3" x 4', 30 socks/package



Poly blend-filled Oil-Only Socks contain and soak up petroleumbased fluids fast while repelling water.

- Absorb Oils, Repel Water By selectively absorbing petroleum-based liquids and not water, these Socks take in more oil and can be left on the job longer. They also float for cleanup of waterborne hydrocarbons.
- Contain and Soak Up Leaks or Spills Ideal for surrounding spilled fluids or wrapping around leaky machines. Easy and convenient to put into place. Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards. Flexible to conform around machine bases and offer a snug fit with no seepage.
- Color-Coded Color-coding helps you visually identify the right sorbent for your needs. White designates Oil-Only sorbency and makes it easy to identify when saturated.

WSO430 Specifications

Dimensions:	ext. dia. 3" x 4' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	30 socks per package
Color:	White
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly
	Blend Filler
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 106.6 oz. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 121.9cm L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 3.2 L per sock
Weight:	13.6 kg



Online: spilltech.com Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other)



WSO430 Technical Information

Warnings & Restrictions:

Color Variance Notice Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS)









Oil-Only Poly Blend Socks #WSO815 - 3" x 8', 15 socks/package



Poly blend-filled Oil-Only Socks contain and soak up petroleumbased fluids fast while repelling water.

WSO815 Specifications

Dimensions:	ext. dia. 3" x 8' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	15 socks per package
Color:	White
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly
	Blend Filler
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 1.7 gal. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 2.4m L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 6.4 L per sock
Weight:	13.6 kg







WSO815 Technical Information

Warnings & Restrictions:

Color Variance Notice Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS)









Oil-Only Poly Blend Socks #WSO1210 - 3" x 12', 10 socks/package



Poly blend-filled Oil-Only Socks contain and soak up petroleumbased fluids fast while repelling water.

WSO1210 Specifications

Dimensions:	ext. dia. 3" x 12' L
Shipping	22" W x 25" L x 18.25" H
Dimensions:	
Sold as:	10 socks per package
Color:	White
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly
	Blend Filler
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 2.5 gal. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 3.7m L
Shipping	55.9cm W x 63.5cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 9.5 L per sock
Weight:	13.6 kg



Online: spilltech.com Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other)



Email: sales@spilltech.com

6455 East Johns Crossing, Suite 375 • Johns Creek GA 30097 © 2021 SpillTech Environmental Corporation. All rights reserved.

WSO1210 Technical Information

Warnings & Restrictions:

Color Variance Notice Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS)









Universal Cellulose Socks #GCSO815 - 3" x 8', 15 socks/package



<H4>***This item will be discontinued once inventory is depleted. Replacement item will be: <u>GSO815</u>. Please make a note of this change in your internal systems.***</H4>

- A single 8' Sock can absorb more than two gallons of oils, coolants, solvents or water, making it a true top performer
- Ideal for surrounding spilled fluids or wrapping around leaky machines
- Easy and convenient to put into place
- Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards
- Very flexible to conform around machine bases and offer a snug fit with no seepage
- Color-coding helps you visually identify the right sorbent for your needs. Gray signifies Universal sorbency

GCSO815 Specifications

Dimensions:	ext. dia. 3" x 8' L
Shipping	22" W x 24" L x 16.5" H
Dimensions:	
Sold as:	15 socks per package
Color:	Gray
Composition:	Cellulose Filler/Polypropylene Sleeve
Absorbency:	Up to 34 gal. per package
Absorbency per:	Up to 2.27 gal. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 2.4m L
Shipping	55.9cm W x 61cm L x 41.9cm H
Dimensions:	
Absorbency:	Up to 128.7 L per package
Absorbency per:	Up to 8.6 L per sock
Weight:	13.6 kg







GCSO815 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)





Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)



Universal Cellulose Socks #GCSO1210 - 3" x 12', 10 socks/package



<H4>***This item will be discontinued once inventory is depleted. Replacement item will be: <u>GSO1210</u>. Please make a note of this change in your internal systems.***</H4>

- A single 12' Sock can absorb more than three gallons of oils, coolants, solvents or water, making it a true top performer
- Ideal for surrounding spilled fluids or wrapping around leaky machines
- Easy and convenient to put into place
- Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards
- Very flexible to conform around machine bases and offer a snug fit with no seepage
- Color-coding helps you visually identify the right sorbent for your needs. Gray signifies Universal sorbency

GCSO1210 Specifications

Dimensions:	ext. dia. 3" x 12' L
Shipping	21" W x 25.5" L x 21.5" H
Dimensions:	
Sold as:	10 socks per package
Color:	Gray
Composition:	Cellulose Filler/Polypropylene Sleeve
Absorbency:	Up to 34 gal. per package
Absorbency per:	Up to 3.4 gal. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 3.7m L
Shipping	53.3cm W x 64.8cm L x 54.6cm H
Dimensions:	
Absorbency:	Up to 128.7 L per package
Absorbency per:	Up to 12.9 L per sock
Weight:	13.6 kg







GCSO1210 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)





Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)