



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 15

Loctite 3430 Part A

SDS No. : 298562
V009.0

Revision: 12.01.2022
printing date: 19.04.2022

Replaces version from: 02.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 3430 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000
Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700)

Bisphenol-F epichlorhydrin resin; MW<700
Bisphenol A diglycidyl ether polymer

Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:

"****" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***

Precautionary statement: Prevention

P273 Avoid release to the environment.
P280 Wear protective gloves.

Precautionary statement: Response

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6		20- 40 %	Skin Sens. 1 H317 Eye Irrit. 2 H319 Skin Irrit. 2 H315 Aquatic Chronic 2 H411
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	01-2119454392-40	20- 40 %	Skin Irrit. 2; Dermal H315 Skin Sens. 1 H317 Aquatic Chronic 2 H411
Bisphenol A diglycidyl ether polymer 25085-99-8		20- 40 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Aquatic Chronic 2 H411 Eye Irrit. 2 H319

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Epoxy adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

None

Occupational Exposure Limits

Valid for
Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (freshwater)		0,003 mg/l				
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (marine water)		0,0003 mg/l				
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sewage treatment plant (STP)		10 mg/l				
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sediment (freshwater)				0,294 mg/kg		
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sediment (marine water)				0,0294 mg/kg		
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Soil				0,237 mg/kg		
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (intermittent releases)		0,0254 mg/l				
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Air						no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m ³	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	dermal	Acute/short term exposure - local effects		0,0083 mg/cm ²	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m ³	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid liquid transparent
Odor	odourless
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 200 °C (> 392 °F)
Flash point	> 100,0 °C (> 212 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density	1,17 g/cm ³
()	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	Not miscible

(Solvent: Water)	
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	19.000 - 25.000 mPa.s
(Cone and plate; 25 °C (77 °F); speed of rotation: 1 min-1; Shear gradient: 10 s-1)	
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.
 Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Bisphenol-F epichlorhydrin resin; MW <700 9003-36-5	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Bisphenol A diglycidyl ether polymer 25085-99-8	LD50	> 2.000 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol A diglycidyl ether polymer 25085-99-8	LD50	> 2.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating	4 h	rabbit	not specified
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study/ Route of administration	Metabolic activation/ Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity/ Carcinogenicity Studies)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity/ Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	NOAEL P \geq 50 mg/kg NOAEL F1 \geq 750 mg/kg NOAEL F2 \geq 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Bisphenol-F epichlorhydrin resin; MW $<$ 700 9003-36-5	NOAEL P $>$ 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two-generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol-F epichlorhydrin resin; MW $<$ 700 9003-36-5	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bispheno-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol-F epichlorhydrin resin; MW $<$ 700 9003-36-5	LC50	5,7 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol A diglycidyl ether polymer 25085-99-8	LC50	2 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bispheno-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW $<$ 700 9003-36-5	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol A diglycidyl ether polymer 25085-99-8	EC50	2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bispheno-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol-F epichlorhydrin resin; MW $<$ 700 9003-36-5	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol A diglycidyl ether polymer 25085-99-8	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol A diglycidyl ether polymer 25085-99-8	EC50	> 11 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol A diglycidyl ether polymer 25085-99-8	NOEC	4,2 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Bisphenol A diglycidyl ether polymer 25085-99-8	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol/ water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information
--

14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3,00 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 20

Loctite 3430 Part B

SDS No. : 205861
V012.1

Revision: 12.01.2022
printing date: 19.04.2022

Replaces version from: 18.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 3430 Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Epoxy Hardener

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000
Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity	Category 4
H302 Harmful if swallowed. Route of Exposure: Oral	
Skin corrosion	Sub-category 1A
H314 Causes severe skin burns and eye damage. Serious eye damage	Category 1
H318 Causes serious eye damage. Skin sensitizer	Category 1
H317 May cause an allergic skin reaction. Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

2,2'-[1,2-ethanediy lbis(oxy)]bis(ethanethiol)

3,3'-Oxy bis(ethyleneoxy)bis(propylamine)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700)

Signal word:

Danger

Hazard statement:H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.**Precautionary statement:**

"****" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***

**Precautionary statement:
Prevention**P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.**Precautionary statement:
Response**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor.**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2,2'-[1,2-ethanediy]bis(oxy)bis(ethanethiol) 14970-87-7	239-044-2 01-2120768482-47	10- 20 %	Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Acute Tox. 3; Oral H301 Acute Tox. 4; Inhalation H332
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	224-207-2 01-2119963377-26	5- < 10 %	Skin Corr. 1B H314 Eye Dam. 1 H318 Skin Sens. 1 H317
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	234-148-4 01-2119970376-29	5- < 10 %	Acute Tox. 4; Oral H302 Skin Corr. 1A H314 Skin Sens. 1B H317
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6		1- < 5 %	Skin Sens. 1 H317 Eye Irrit. 2 H319 Skin Irrit. 2 H315 Aquatic Chronic 2 H411
Benzyl dimethylamine 103-83-3	203-149-1 01-2119529232-48	0,1- < 1 %	Acute Tox. 4; Dermal H312 Skin Corr. 1B H314 Flam. Liq. 3 H226 Aquatic Chronic 2 H411 Acute Tox. 4; Oral H302 Acute Tox. 3; Inhalation H331

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

Causes burns.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

7.3. Specific end use(s)
Epoxy Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

None

Occupational Exposure Limits

Valid for
Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	aqua (freshwater)		0,00076 mg/l				
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	aqua (marine water)		0,000076 mg/l				
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	sewage treatment plant (STP)		6,74 mg/l				
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	sediment (freshwater)				0,0047 mg/kg		
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	sediment (marine water)				0,00047 mg/kg		
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	Soil				0,0005 mg/kg		
2,2'-[1,2-Ethanediy l bis(oxy)]bis(ethanethiol) 14970-87-7	aqua (intermittent releases)		0,0076 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (freshwater)		0,22 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (marine water)		0,022 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (intermittent releases)		2,2 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sewage treatment plant (STP)		125 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (freshwater)				1,1 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (marine water)				0,11 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Soil				0,091 mg/kg		
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	aqua (freshwater)		9,2 µg/l				
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	aqua (marine water)		0,92 µg/l				
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	aqua (intermittent releases)		92 µg/l				
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	Sewage treatment plant		18,1 mg/l				
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	sediment (freshwater)				0,0336 mg/kg		
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	sediment (marine water)				0,00336 mg/kg		
N ⁻ -(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	Soil				0,00132 mg/kg		
Benzyl dimethylamine 103-83-3	aqua (freshwater)		0,0048 mg/l				
Benzyl dimethylamine 103-83-3	aqua (marine water)		0,00048 mg/l				
Benzyl dimethylamine 103-83-3	aqua (intermittent releases)		0,0134 mg/l				
Benzyl dimethylamine 103-83-3	sewage treatment plant (STP)		534 mg/l				
Benzyl dimethylamine 103-83-3	sediment (freshwater)				0,071 mg/kg		
Benzyl dimethylamine 103-83-3	sediment (marine water)				0,0071 mg/kg		
Benzyl dimethylamine 103-83-3	Soil				0,0114 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-[1,2-Ethanediybis(oxy)]bis(ethanethiol) 14970-87-7	Workers	inhalation	Long term exposure - systemic effects		1,23 mg/m ³	
2,2'-[1,2-Ethanediybis(oxy)]bis(ethanethiol) 14970-87-7	Workers	dermal	Long term exposure - systemic effects		1,75 mg/kg	
2,2'-[1,2-Ethanediybis(oxy)]bis(ethanethiol) 14970-87-7	General population	inhalation	Long term exposure - systemic effects		0,22 mg/m ³	
2,2'-[1,2-Ethanediybis(oxy)]bis(ethanethiol) 14970-87-7	General population	oral	Long term exposure - systemic effects		0,125 mg/kg	
2,2'-[1,2-Ethanediybis(oxy)]bis(ethanethiol) 14970-87-7	General population	dermal	Long term exposure - systemic effects		0,625 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - systemic effects		59 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Acute/short term exposure - systemic effects		176 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - local effects		13 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	dermal	Long term exposure - systemic effects		8,3 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - systemic effects		17 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - systemic effects		52 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - local effects		0,5 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - local effects		6,5 mg/m ³	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	oral	Long term exposure - systemic effects		5 mg/kg	
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Workers	inhalation	Long term exposure - systemic effects		0,35 mg/m ³	
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Workers	dermal	Long term exposure - systemic effects		0,05 mg/kg	
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	General population	inhalation	Long term exposure - systemic effects		0,65 mg/m ³	
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	General population	oral	Long term exposure - systemic effects		0,2 mg/kg	
Benzyl dimethylamine 103-83-3	Workers	dermal	Long term exposure - systemic effects		2,3 mg/kg	
Benzyl dimethylamine 103-83-3	Workers	inhalation	Long term exposure - systemic effects		14,6 mg/m ³	
Benzyl dimethylamine 103-83-3	Workers	inhalation	Long term exposure - local effects		1 mg/m ³	
Benzyl dimethylamine 103-83-3	General population	dermal	Long term exposure - systemic effects		1,25 mg/kg	
Benzyl dimethylamine 103-83-3	General population	oral	Long term exposure -		1,25 mg/kg	

			systemic effects			
Benzylidimethylamine 103-83-3	General population	inhalation	Long term exposure - systemic effects		43,75 mg/m ³	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid liquid Clear
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 230 °C (> 446 °F)
Flash point	> 100,0 °C (> 212 °F); no method
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable

Explosive limits	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	< 700 mbar
Relative vapour density:	No data available / Not applicable
Density (g/cm ³)	1,1 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Acetone)	Soluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Cone and plate; 25 °C (77 °F); Shear gradient: 10 s ⁻¹)	19.000 - 26.000 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reacts with strong oxidants.
Acids.
Reaction with strong acids.
Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.
Rapid polymerisation may generate excessive heat and pressure.
May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	LD50	> 50 - 300 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	LD50	3.160 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	LD50	1.669 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Benzyl dimethylamine 103-83-3	LD50	353 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	LD50	> 2.150 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Benzyl dimethylamine 103-83-3	LD50	1.477 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
2,2'-[1,2-ethanediy]bis(oxy)]bis(ethanethiol) 14970-87-7	LC50	1,34 mg/l	dust/mist	4 h	rat	not specified
Benzyl dimethylamine 103-83-3	LC50	2,052 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤700) 25068-38-6	not irritating	4 h	rabbit	not specified

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2,2'-[1,2-ethanediy]bis(oxy)]bis(ethanethiol) 14970-87-7	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤700) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
3,3'-Oxybis(ethyleneoxy)bis(popylamine) 4246-51-9	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
3,3'-Oxybis(ethyleneoxy)bis(popylamine) 4246-51-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3,3'-Oxybis(ethyleneoxy)bis(popylamine) 4246-51-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
3,3'-Oxybis(ethyleneoxy)bis(popylamine) 4246-51-9	NOAEL P 600 mg/kg	screening	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	NOAEL P ≥ 50 mg/kg NOAEL F1 ≥ 750 mg/kg NOAEL F2 ≥ 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	NOAEL < 100 mg/kg	oral: gavage	59 days daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤700) 25068-38-6	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	LC50	5,7 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	LC50	> 215 - 464 mg/l	96 h	Leuciscus idus	DIN 38412-15
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzyl dimethylamine 103-83-3	LC50	37,8 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	EC50	0,76 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	EC50	218 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
N-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	EC50	9,2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Benzyl dimethylamine 103-83-3	EC50	> 100 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Benzyl dimethylamine 103-83-3	NOEC	0,789 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	EC50	3,11 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Algal Growth Inhibition Test)
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	EC10	0,51 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Algal Growth Inhibition Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	EC50	666 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	NOEC	15,6 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Algal Growth Inhibition Test)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Algal Growth Inhibition Test)
Benzyl dimethylamine 103-83-3	EC50	1,34 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Benzyl dimethylamine 103-83-3	NOEC	0,24 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	EC50	772,1 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	EC10	152,5 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemmtest)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	EC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Benzyl dimethylamine 103-83-3	EC10	534 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemmtest)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	not readily biodegradable.	aerobic	< 10 %	28 d	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	not inherently biodegradable	aerobic	< 20 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	not readily biodegradable.	aerobic	0 %	60 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	readily biodegradable		100 %	28 d	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Benzyl dimethylamine 103-83-3	not readily biodegradable.	aerobic	0 - 2 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Benzyl dimethylamine 103-83-3	> 2,1 - 22	42 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	1,66	55 °C	OECD Guideline 117 (Partition Coefficient (n-octanol/ water), HPLC Method)
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	-1,25	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol/ water), Shake Flask Method)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	-0,47	25 °C	other (calculated)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Benzyl dimethylamine 103-83-3	1,98		EU Method A.8 (Partition Coefficient)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Benzyl dimethylamine 103-83-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Disposal of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information
--

14.1. UN number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

14.2. UN proper shipping name

ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-oxybis(ethyleneoxy)bis(propylamine))
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-oxybis(ethyleneoxy)bis(propylamine))
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-oxybis(ethyleneoxy)bis(propylamine))
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-oxybis(ethyleneoxy)bis(propylamine),2,2'-[1,2-Ethanediy lbis(oxy)]bis(ethanethiol))
IATA	Amines, liquid, corrosive, n.o.s. (N,N'-Dimethyldipropyltriamine,3,3'-oxybis(ethyleneoxy)bis(propylamine))

14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.