
Technical specifications**Safescape Elite 20 m KIT****Reference :**

- 1029350

**Description**

Miller safescape Kit with wheel + handle and 20 M rope supplied into a bag with 1 anchor sling.

Thanks to its durable high-quality anodized aluminium housing, our units remains in optimum condition of use, even in the toughest environments.

8000m descent for 100kg, maximum descent height of 500m, use in emergency by 2 people weighing up to 250kg.

Recertification by factory or Miller Service Point is required only after seven years, thanks to its robust and highly resistant components.

Available in several lengths (see references below) and also a range of accessories for rescuing.

Features

- Safescape + wheel and handle with 20 M rope ref 1029150

Housing :Anodized Aluminium

Mécanisme : Aluminium Pulley

Weight (without rope) : 1.8 Kg

Karabiner : Dim. : 134 * 75 mm, Opening : 20 mm

Descend speed: 1m / second

Miller Safescape ELITE complies with the new EN 341/2008 standard



by Honeywell

- Anchor Sling 1,2 m ref 1008363
 - Raw material : polyamide webbing
 - Width : 25 mm
 - Breaking strength : > 2200 daN
 - Complies to the standard:
 - EN 795 : Anchorage devices
 - ANSI Z359.1 A10.32-2004
 - OSHA 1929.502

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

SPERIAN FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com