Europe / Africa



PRODUCT NUMBER: 1018014 TURBOLITE webbing 2m webbing 2m - Scaf hook + Twistlock



Overview

Reference Number 1018014

Product Type Fall Protection

Range Fall Arrest Blocks and Winches

Brand Miller by Honeywell

Industry

Industry
Building and Construction

Product Use

The TurboLite is the first affordable alternative to shock-absorbing lanyards. It provides a safe alternative requiring less fall clearance.

Features & Benefits

Feature

* Built-in web load indicator identifies when the unit needs removed from services

* Quick activating Patent Pending Braking System.

- * Compact and lightweight provides 2m working capacity lifeline
- * Engineered webbing for greater abrasion resistance and long service life (vectran / polyester webbing).
- * Lightweight, high-strength, impact-resistant nylon housing for maximum durability
- * Built-in swivel prevents lifeline from twisting
- * No annual factory recertification required

TURBOLITE webbing 2m - 1018014

* Rated for up to a 136 kg user Rated for up to a 100kg user (use in down level)

Benefit

Adapted to all situation when working with low space clearance.

Can be used in Fall Factor 2 (below the back D ring and not lower than foot level).

Can be used on both side.

Technical Description

External

Housing high impact nylon

Hub shock-absorbing engineered co-polymer

Webbing Vectran core (25.4mm x 1.5mm)

Connectors Carabiners:

Scaff Hook (opening: 65mm) raw material: aluminium

Twistlock carabiner (opening: 18mm) raw material: stainless steel

Performance Weight (kg)

1.252 kg

Complementary Information EN 360

Certifications

E.C. Declaration of Conformity

EC Category PPE 3

Quality Assurance ISO 9001 / 2000

EC Attestation

EC Attestation Number 0082/544/160/12/08/0430

Additional Information

User Manual NT90022859 IND D

User Information Sheet User manual

Packaging

© Honeywell International Inc.