TECHNICAL SPECIFICATION

EYE AND FACE PROTECTION



EVOGuard®C2 Industrial Visor

EVOGuard®C2 Industrial Visor / Code: ADA250-060-000



DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and EVO® helmet range, the C2 visor offers up to AT rated impact protection and is also suitable for use with the Force™8 half mask and P3 filters.

OPTIONS

EVOGuard®C2 Industrial Visor (ADA250-060-000)

DOWNLOADS

Image Pack (ZIP)

Declaration of Conformity (PDF)

VIDEO

www.youtube.com/watch?v=_VnTgBRRT9E









FEATURES



Helmet & Browguard Integration

Fully compatible with EVO® helmet and the EVOGuard™ Browguard system. Not including EVO®Vista™ or EVO®6100 ranges



Compatibility

EVOGuard™ visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Impact

Five high performance visors offering up to A rated impact resistance when fitted to a safety helmet and fully compatible with EVOGuard™ browguard for medium energy impact protection.



Coverage

EVOGuard™ visors provide comprehensive facial coverage without limiting movement. EVOGuard™ MAX visors offer enhanced coverage with an integral chinguard.



UV Protection

Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.

COMPATIBLE PRODUCTS

EVO®2 Mid Peak OneTouch™ Slip Ratchet Non Vented

EVO®2 Mid Peak OneTouch™ Slip Ratchet Vented

EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented

EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman

EVO®3 Micro Peak OneTouch™ Slip Ratchet Vented

EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented

EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented Linesman

SAFETY STANDARDS

EN 166

EN 170

SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number



LIGHT TRANSMISSION BREAKDOWN Lens Shade number

1.2

Manufacturer's Trademark




JSP Dagger



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 - Class 3 - Low quality for exceptional use)



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection





Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles

B - When Fitted To EVOGuard® Browguard



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5?C and +55?C) Optional



Protection from Liquid Splash 3

Resistance to Molten Metals and Hot Solids (optional)



Resistance to Surface Damage by Fine Particles (optional) Κ



Resistance to fogging (optional)



Visor Length 18.5cm



BSI Kitemark

Yes

Material

Polycarbonate Shield



Product Weight 185q





Yes



Supplied With: EVO® 2,3,5,DS,Lite,Skyworker™ Arms. EVO8/EVOLite Badgeholder Arms. EVOGuard® **Browguard Mounting System**

APPLICATIONS

Aerospace

Agricultural

- Arborist
- Farming
- Grain Stores
- Landscaping

Airports

Ground Maintenance


Construction and Infrastructure

Facilities Management













EVO®3 Micro Peak Revolution® Wheel Ratchet Vented

EVO®3 Mid Peak Revolution® Wheel Ratchet Non Vented

EVO®3 Mid Peak OneTouch™ Slip Ratchet Non Vented

EVO®3 Mid Peak OneTouch™ Slip Ratchet Vented

EVO®3 Mid Peak Revolution® Wheel Ratchet Vented

EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented

EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet

EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented

EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented Linesman

EVO®8 Mid Peak Wheel Ratchet Non Vented

EVO®8 Mid Peak Wheel Ratchet Non Vented Linesman

EVO®8 Mid Peak Wheel Ratchet Vented

EVOLite® Micro Peak OneTouch™ Slip Ratchet Non Vented

EVOLite® Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman

EVOLite® Micro Peak OneTouch™ Slip Ratchet Vented

EVOLite® Micro Peak Revolution® Wheel Ratchet Non Vented

EVOLite® Micro Peak Revolution® Wheel Ratchet Non Vented Linesman

EVOLite® Micro Peak Revolution® Wheel Ratchet Vented

EVOLite® Micro Peak Revolution® Wheel Ratchet Vented Linesman

EVOLite® Mid Peak OneTouch™ Slip Ratchet Non Vented

EVOLite® Mid Peak OneTouch™ Slip Ratchet Vented

EVOLite® Mid Peak Revolution® Wheel Ratchet Non Vented

EVOLite® Mid Peak Revolution® Wheel Ratchet Vented

EVOLite® Skyworker™ Micro Peak Revolution®Wheel Ratchet Vented

Sonis® Compact Helmet Mounted Ear Defenders

Sonis®1 Helmet Mounted Ear Defenders

Sonis®3 Helmet Mounted Ear Defenders

ACCESSORIES

PPE Cleaning Station & Accessories

Food and Drink Manufacturing

Law Enforcement

- Armed Forces
- Police
- Prison
- UN Forces

Manufacturing

- Automotive
- Cosmetics
- Foundries and Metals
- Injections Moulding
- Packaging
- Paper
- Pharmaceutical
- Wood and Timber
- Container
- Dockyard
- Fisheries
- On Board
- Port Authorities
- · Shipyard and Boat Building

Mining, Aggregates and Quarrying

Oil, Gas and Chemical Companies

Rail and Tunnelling

Renewable, Wind and Solar Energy

Scaffolding and Roofing

Sole Trader

- Carpentry
- Electrical
- Gas
- Painting and Decorating
- Water and Plumbing

Utilities Contractors

- Electrical
- Gas
- Telecomms
- TM Companies
- Water

RANGE









