

Affordable, durable protection for clean environments

TouchNTuff® 93-300 is an affordable, clean nitrile glove that delivers superior protection and durability without compromising comfort.

- Compatible with Class 100 (ISO 5) / Grade A Cleanroom Environments
- Proprietary Ansell nitrile offers superior chemical splash protection
- Affordable without compromising comfort
- Robust design resists punctures and tears
- Silicone-free for product protection



Industries

- Biotechnology Manufacturing

Recommended For

- Transferring liquids



TECHNICAL DATA SHEET

PRODUCT INFORMATION

| | |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | 93-300 |
| Material | Nitrile |
| Color | Green |
| Shape | Ambidextrous |
| Cuff | Beaded |
| Manufacturing/QMS Audit Standards | ISO 9001:2008 |
| Regulatory/Standards Compliance | ASTM D6319, Category III, EAC TP TC 019:2011, EN 420:2003 + A1:2009, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 421:2010, FDA21 CFR 177-2600, ISO 13485, ISO 14001, ISO 9001 |
| Packaging | 50 gloves per vacuum sealed polybag 2 polybags per master polybag 10 master poly bags per poly lined case |
| Storage | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country of Origin | Thailand |
| Available sizes | S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10) |
| Powder Content | Powder-Free |
| External Glove Surface | Textured Fingers |
| Sterilization Method | Not Applicable |
| Cleanroom Class | Class 100/ISO 5 & EU GMP Grade A |
| Shelf Life | 3 Years |
| Tested for use with Chemotherapy Drugs | No |
| Protein Level | N/A: contains no natural rubber latex |
| Anti-static | Yes |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|--------------------------------------------------------------|-------------------------------------|---------------|---------------------|
| Length (mm/in) | 300 / 12 | | EN 420/ASTM D3767 |
| Freedom from Holes | 1.5 AQL | | EN 455-1/ASTM D3577 |
| Typical Particle Count ≥0.5µm (counts / cm ²) | ≤ 1,500 particles / cm ² | | IEST-RP-CC005.4 |
| Minimum Single Wall Palm Thickness (mm/mil) | 0.13 / 5.1 | | EN 420/ASTM D3767 |
| Minimum Single Wall Finger Thickness (mm/mil) | 0.16 / 6.3 | | EN 420/ASTM D3767 |
| Minimum Single Wall Cuff Thickness (mm/mil) | 0.08 / 3.1 | | EN 420/ASTM D3767 |
| | Before Ageing | During Ageing | |
| Ultimate tensile strength (MPa) | ≥ 14 | ≥ 14 | ASTM D412-06a |
| Force at Break (N) | ≥ 9 | ≥ 9 | EN 455-2 |

ORDERING INFORMATION

| | SIZE | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------|-------------|-------------|-------------|-------------|---------------|
| 93-300 | REORDER NO. | 556079 | 556080 | 556081 | 556082 |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
US T: +1 800 800 0444
US F: +1 800 800 0445
CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133


Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890

Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.