MID PEAK - SLIP RATCHET - NON-VENTILATED

HEAD PROTECTION

SPECIFICATION

TECHNICAL

PRODUCT CODE: AJE030-000- 00

THE EVO2® OFFERS THE MOST ECONOMICAL TOP LEVEL PROTECTION



CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

Meets optional Molten Metal requirements

EU Type Examination Certificate Number 676976

Low dome profile

Helmet offers electrical insulation

Compatible with other JSP safety products

Available in a choice of colours

Company personalisation available by printing

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com .























TECHNICAL **SPECIFICATION**

HEAD PROTECTION

PRODUCT CODE: AJE030-000- 00

THE EVO2® OFFERS THE MOST ECONOMICAL TOP LEVEL PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 3.8kg (Approx.)



DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 350g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet













06 Red



HEIGHT: 450mm

HELMET FEATURES

EN STANDARD	EN397 EN50365	Yes Yes
PERFORMANCE	Impact Resistance Electrical Insulation	Yes 50 Joules Yes: EN397 440V EN50365 1000V
TEMPERATURE RESISTANCE	Low Temperature Molten Metal (MM)	Yes: EN397 -30°C FOCT P 50460-92 -30°C Yes
SHELL MATERIAL	HDPE Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	HDPE LDPE	Yes Yes
OPTIONS	Universal Accessories Reflective CR2 option	Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
CHINSTRAP	4 pts	Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com .















