

# COBRA

## MODULARITY & FUNCTIONALITY

The essential all rounder with a panoramic visual field! Wrap-around fit without any visual interference, COBRA offers 180° vision and perfect optical quality. The option of swapping the temples for an adjustable strap and foam seal means COBRA is a highly versatile model.

SUPPLIED WITH : Adjustable cord

25 G

+ 1 PRODUCT = 2 USES (SPECTACLES OR GOGGLES VERSION)

+ WIDE RANGE OF LENS SHADES FOR MULTIPLE APPLICATIONS

+ PIVOTING TEMPLES TO ADJUST AND IMPROVE PROTECTION

+ PLATINUM COATING : ANTI-SCRATCH & ANTI-FOG



### TECHNOLOGIES

ESP

HD

PLATINUM

PLATINUM LITE

### VERSIONS



COBFTPSI

COBPSI



COBFSPSI

COBCSP



COBHDPi

COBCONT



COBPSF

OCCOBPSI



COBESP



CERTIFIED FOR EXPLOSIVE ATMOSPHERES  
ATEX IIA, IIB, IIC, IIIA, IIIB, IIIC, AREA 1,2,20,21,22

COBRA						
USE	VERSION	REFERENCE	LENS MARKING	FRAME MARKING	COATING	STANDARD
h	CLEAR	COBFTPSI	2C-1.2 ☞ 1 BT KN €€	☞ EN166 FT €€	PLATINUM	EN166-EN170
h	CLEAR	COBFSPSI	2C-1.2 ☞ 1 BT KN €€	☞ EN166 3 BT €€	PLATINUM	EN166-EN170
h	HD	COBHDMI	2C-1.2 ☞ 1 BT €€	☞ EN166 FT €€	HYDROPHOBIC / ANTIRE-FLECTIVE / ANTI-SCRATCH	EN166-EN170
h	CLEAR	COBPSI	2C-1.2 ☞ 1 BT KN €€	☞ EN166 FT €€	PLATINUM	EN166-EN170
h*	COPPER	COBCSP	5-1.4 ☞ 1 BT KN €€	☞ EN166 FT €€	PLATINUM	EN166-EN172
h	GRADIENT BRONZE	COBCONT	5-1.1/1.4 ☞ 1 BT €€	☞ EN166 FT €€	PLATINUM LITE	EN166-EN172
h*	COPPER FLASH	COBESP	5-1.4 ☞ 1 BT €€	☞ EN166 FT €€	PLATINUM LITE	EN166-EN172
*	SMOKE	COBPSF	5-3.1 ☞ 1 BT KN €€	☞ EN166 FT €€	PLATINUM	EN166-EN172
h	CLEAR	OCCOBPSI	2C-1.2 ☞ 1 BT €€		PLATINUM LITE	EN166-EN170

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO €€ STANDARDS WILL BE SENT ON REQUEST.

PACKAGING & EAN13 CODE		
SINGLE:	INNER BOX:	OUTER PACK:
Size: 28.5 x 12.2 x 5.5 mm	Size: 24x18x9 cm Weight: 0.65 kg	Size: 60 x 50 x 40 cm Weight: 14.5 kg
366074006921	3660740106928 -10 pcs	3660740206925 -200 pcs
3660740005986	3660740105983 -10 pcs	3660740205980 -200 pcs
3660740006013	3660740106010 -10 pcs	3660740206017 -200 pcs
3660740006129	3660740106126 -10 pcs	3660740206123 -200 pcs
3660740008048	3660740108045 -10 pcs	3660740208042 -200 pcs
3660740005993	3660740105990 -10 pcs	3660740205997 -200 pcs
3660740006006	3660740106003 -10 pcs	3660740206000 -200 pcs
3660740006136	3660740106133 -10 pcs	3660740206130 -200 pcs
3660740006020	3660740106027 -25 pcs	3660740206024 -300 pcs
CUSTOM CODE: 9004901000		



CERTIFIED FOR EXPLOSIVE ATMOSPHERES  
ATEX IIA, IIB, IIC, IIA, IIB, IIC, AREA 1.2, 20, 21, 22

GENERAL SPECIFICATIONS			
LENS	POLYCARBONATE - 2.2 MM	FOAM	EVA
CURVE	9 - VERY CURVED	STRAP	NYLON POLYESTER
FRAME	NYLON/PC/TPR - RIMLESS	OPTIONAL	FOAM AND STRAP KIT

OPTIONAL ACCESSORIES				
REFERENCE	DESCRIPTION	SINGLE	INNER BOX	OUTER PACK
KITFSCOB	FOAM AND STRAP KIT	366074006037	3660740106034	3660740206031



KNOW MORE ABOUT MARKINGS:

OR SCAN:

### CLEANING & STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 03-21-2022

[bolle-safety.com](http://bolle-safety.com)

**Europe Headquarters**  
34 rue de la Soie  
69100 Villeurbanne  
France  
P : 00 33 (0) 4 78 85 23 64

**U.K. & Ireland**  
Unit C83- Barwell Business Park  
Leatherhead Road- Chessington  
Surrey - KT9 2NY- UK  
P : 00 44 (0)208 391 4700

**USA Office**  
2810 Caribou Court, Suite 160  
Carlsbad, CA 92010  
United States of America  
P : 800 222 6553

**Asia-Pacific Office**  
32-40 Fairchild Street  
Heatherton VIC 3202  
Australia  
P : 1300 138 098

