Europe / Africa Partners | Where To Buy





PRODUCT NUMBER: 2095020

POWERCOAT® 950-20 NEOFIT

Protection against a wide range of chemical products (detergents, some solvents, acids and bases).

Honeywell

Overview

Reference Number

2095020

Product Type

Gloves

Range

Chemical Protection

Line

Heavy chemical

Brand

Honeywell

Brand formerly known as

SPERIAN

Industry

- Agriculture Automotive and Part Manufacturer Building and Construction Chemical Industries
- Industrial Cleaning
 Maintenance
 Petro-chemical
 Water treatment
 Wood Industries

Product Use

Protection against a wide range of chemical products (detergents, some solvents, acids and bases).

Features & Benefits

Feature

Black neoprene Unsupported glove Cotton flocked interior Diamond finish

Benefit

COMFORT

Neoprene offers high flexibility

The cotton flocked interior provides the user with greater comfort and makes it easier to slip in the glove. Its diamond finish provides a better grip in a damp environment.

POWERCOAT® 950-20 NEOFIT - 2095020

RESISTANCE

Neoprene provides chemical and mechanical resistance.

It resists to acids, bases and solvents as well as industrial adhesives.

It is suitable for a wide range of chemicals.

SAFETY

Category III glove for constant quality.

The cuff helps to protect a large part of the forearm.

Technical Description

Description

CE CATEGORY: III Irreversible risks In accordance with standards: EN 420-2003 EEC Basic standard EN 388-2003 Mechanical risks EN 374-2003 Chemical risks

CHARACTERISTICS:

Unsupported polypropylene glove

Cotton flock inside Diamond-pattern finish

Product Technology

Dipped Gloves

Glove/liner color

Black

Coating Color

neoprene and cotton

Length

33 cm

Thickness

0.72 mm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes

7 to 11

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	2
Cutting resistance (Coupe test)	0
Tear resistance	0
Puncture resistance	1
Cutting resistance (TDM test)	X

EN ISO 374-1 Resistance to

Resistance to permeation by chemicals Type B - JKLOT

EN 374-3 Resistance to

Resistance to permeation by chemicals	AKL
---------------------------------------	-----

Certifications

EU Category PPE

3

EU Certification

0075/797/162/03/19/1041

Additional Information

User Manual

UI 104

User Information Sheet

104

Maintenance

Storage Information

Individual packaging.
Minimum sale packaging 10 pairs.
Boxes of 100 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.

© Honeywell International Inc.