

# Butoject® 898



## APPLICATION

- › printing industry
- › laboratories
- › manufacturing of paints and varnishes
- › chemical industry
- › metal and plastics processing
- › recycling and waste disposal
- › cleaning and maintenance
- › fire brigades and forces

## QUALITIES AND ADVANTAGES

- › very good protection against extremely aggressive chemicals
- › excellent wearing comfort
- › very good temperature flexibility
- › good mechanical resistance
- › high tightness against gas



|                      |                                    |
|----------------------|------------------------------------|
| Article no.          | 898                                |
| Name                 | Butoject® 898                      |
| Material             | butyl                              |
| Description          | rolled edge<br>smooth,<br>powdered |
| Length (mm)          | 340-360                            |
| Total thickness (mm) | 0,7 ± 0,10                         |
| Colour               | black                              |
| Size                 | 8, 9, 10, 11                       |
| Classification       | category III                       |
|                      |                                    |



## FEATURES

- › AQL < 0,65
- › excellent low degradation
- › manufactured by Vulkoject process technology
- › gastight (meets NATO requirements)
- › wide shape makes it possible to wear gloves underneath
- › may be reused for certain chemical groups after a special cleaning process (please consult the KCL-laboratory)
- › can be combined with chemical protective clothing

[www.kcl.de](http://www.kcl.de)  
[sales@kcl.de](mailto:sales@kcl.de)



by Honeywell

## KCL GmbH

Industriepark Rhoen  
 Am Kreuzacker 9  
 36124 Eichenzell  
 Germany  
 Phone +49 6659 87-300  
 Fax +49 6659 87-318