

# **ULTRANE 500**

#### Grip and skin protection for oily environments.





EN388



4121A

CAT.3



0075

EN407



X1XXXX

ISO 13997:

5 N

DEXTERITY EN 420: 5/5

ISO 18889



#### SPECIFIC ADVANTAGES

### Durability

- Excellent abrasion resistance due to the nitrile coating Long lasting and cost effective glove: washable until 3 cleaning cycles (see laundering and drying conditions)
- Color adapted to dirty environements for a prolonged durability.

### Productivity

 Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

### Skin protection

- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free

#### Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### Washability

 Washable 3 times at 40° without any alteration on performances\* to extend lifespan, reduce costs and waste

### Additionnal benefits

Available in vending machine packaging

#### **INDUSTRIES**

- Automotive/mechanical industry
- Mechanical industry
- Other industries
- Glass industry
- Agriculture sector

#### **APPLICATIONS**

- Maintenance in wet environments
- Handling glass sheets
- Re-entry tasks
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil





# **ULTRANE 500**


## LEGENDS

EN388

**MECHANICAL HAZARDS** 



PERFORMANCE LEVELS (X = NOT TESTED)




EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)





Limited flame spread

PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

#### PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
Length (cm)	23-28
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.1E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.4E+11 Ω

## LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	96 pairs/carton

#### **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0075 | CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

\* Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

