



Prod. Ref.	78881-000
Safety cat.	S3 SRC
Range of sizes	36 - 48 (3 - 13)
Weight (sz. 8)	530 g
Shape	A
Width	11

Description: Black water repellent leather shoe, **SANY-DRY**[®] lining, antistatic, anti-shock, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**.

Plus: **COFRA SOFT** footbed, made of scented polyurethane, holed, antistatic, anatomic, soft and comfortable; the shape of the bottom part guarantees impact energy absorption (shock absorber) and high grip; the upper part absorbs moisture and keeps the foot dry. Perfumed sole. Bellows tongue. **TPU toe cap protection**

Suggested uses: Construction, maintenance, industries.

Care and maintenance: Clean after each use and dry off away from direct heat; treat the leather with a suitable shoe-polish. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water.

MATERIALS / ACCESSORIES

Complete shoe	Toe cap: ALUMINIUM made, ultra light, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.3	Shock resistance (clearance after shock)
		5.3.2.4	Compression resistance (clearance after compression)
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1	Penetration resistance
	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges	6.2.2.2	Electric resistance
			- wet
			- dry
	Energy absorption system	6.2.4	Shock absorption
Upper	Black water repellent leather thickness 1,6/1,8 mm	5.4.6	Water vapour permeability
			Permeability coefficient
		6.3.1	Water absorption
			Water penetration
Vamp lining	Textile, breathable, abrasion resistant, colour black Thickness 1,2 mm	5.5.3	Water vapour permeability
			Permeability coefficient
Quarter lining	SANY-DRY [®] , breathable, antibacterial, abrasion resistant, colour orange and black thickness 1,2 mm	5.5.3	Water vapour permeability
			Permeability coefficient
Sole	Antistatic Polyurethane/TPU directly injected in the upper: Outsole: Ice TPU, slipping resistant, abrasion resistant and hydrocarbons resistant. Midsole: Black polyurethane, low density, comfortable and anti-shock.	5.8.3	Abrasion resistance (lost volume)
		5.8.4	Flexing resistance (cut increase)
		5.8.5	Interlayer bond strength
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)
		5.3.5	SRA : ceramic + detergent solution – flat

SAFETY TECHNICAL SPECIFICATIONS

Clause EN ISO 20345:2011	Description	Unit	Cofra result	Requirement
5.3.2.3	Shock resistance (clearance after shock)	mm	16	≥ 14
5.3.2.4	Compression resistance (clearance after compression)	mm	15,5	≥ 14
6.2.1	Penetration resistance	N	To 1100 N	≥ 1100
			No perforation	
6.2.2.2	Electric resistance			
	- wet	M Ω	388	≥ 0.1
	- dry	M Ω	706	≤ 1000
6.2.4	Shock absorption	J	28	≥ 20
5.4.6	Water vapour permeability	mg/cmq h	> 1,2	$\geq 0,8$
	Permeability coefficient	mg/cmq	> 16,3	> 15
6.3.1	Water absorption		13%	$\leq 30\%$
	Water penetration		0,0 g	$\leq 0,2 g$
5.5.3	Water vapour permeability	mg/cmq h	> 6,3	≥ 2
	Permeability coefficient	mg/cmq	> 51,1	≥ 20
5.5.3	Water vapour permeability	mg/cmq h	> 10,3	≥ 2
	Permeability coefficient	mg/cmq	> 82,8	≥ 20
5.8.3	Abrasion resistance (lost volume)	mm ³	35	≤ 150
5.8.4	Flexing resistance (cut increase)	mm	1	≤ 4
5.8.5	Interlayer bond strength	N/mm	> 5	≥ 4
6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	-0,6	≤ 12
5.3.5	SRA : ceramic + detergent solution – flat		0,60	$\geq 0,32$
	SRA : ceramic + detergent solution – heel (contact angle 7°)		0,51	$\geq 0,28$
	SRB : steel + glycerol – flat		0,27	$\geq 0,18$
	SRB : steel + glycerol – heel (contact angle 7°)		0,19	$\geq 0,13$