TECHNICAL DATA SHEET

MALCOLM blue Low ESD S1P No. 729511

Sz. 40 - 48











LABELLING ACCORDING TO STANDARD

Standard for safety footwear EN ISO 20345 S1P Basic requirement for S1P:

 ${f A}$ Antistatic shoe - ${f E}$ Energy absorption in the heel - ${f FO}$ Fuel resistance -

P Penetration resistance - Closed heel area

Additional requirements

SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.

FORM

Safety shoe



Form A - in size 42, the upper height must not exceed 11.2 cm.

AREAS OF APPLICATION

Areas of application

Dry work areas

Industry, storage, transport, assembly etc.

Areas where there is a risk of penetration from pointed and sharp objects (S1P)

Areas where there is a risk of electrostatic discharge (ESDS/ESD)

Workplaces on hard Undergrounds: The revolutionary Infinergy® sole core cushions impacts and provides for a rebound effect when the compressive impulse subsides - for more energy in every step.

FEATURES

ESD equipment

Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.



Certification in accordance with DGUV rule 112-191

Certified for orthopaedic inserts



FEATURES		
Padded upper edge	Excellent wearing comfort: the padded upper edge protects the Actiendon.	hilles
Padded tongue	Excellent wearing comfort: The tongue prevents pressure marks.	
Reflective material	Good visibility in the dark	
Sole core made of Infinergy® by BASF	The sole core consists of expanded, thermoplastic polyurethane in the form of oval foam beads. These stick together and are very light and elastic. This revolutionary technology cushions the impact and bounces back extremely well on pressure, so that the energy can be returned to the wearer. Even under low temperatures of -20 °C, the core maintains its high elasticity.	infinorgy.
Abrasion-resistant toe protection	 Directly applied to the upper in the shoe tip area Excellent wear protection in the shoe tip area Protects the upper in this critical area against premature wear 	
Ergonomic Product IGR certification	The IGR quality seal (Interessengemeinschaft der Rückenschullehrer/-innen e.V. / Association of back specialists) confirms the highly praised features and practical functionality of the tested products. The IGR certification attests the degree of the product's customisability to the physical characteristics of the test person. In accordance with DIN 33419 / EN ISO 15537, the product's usability and ergonomics were tested. Products recommended by IGR e.V. bear the title "Ergonomic Product".	.IGR international action of the contraction of the
Winner Plus X Award	The independent jury for the Plus X Award, the Innovation Prize for Technology, Spot, and Lifestyle, grants a total of seven seals of approval to brands that offer products with a competitive edge in terms of quality and innovation. ELTEN has always seen itself as an innovative business at the cutting edge of technology.	(+X)
UPPER MATERIAL		
Microfibre	 Synthetic material Particularly soft Retains its shape Tear-resistant Quick drying Abrasion-resistant and light 	
Mesh material	 Areas of application S1 Synthetic material Retains its shape Tear-resistant Quick drying Abrasion-resistant and light 	
LINING		
Breathable fabric lining	 Climate-regulating Good ventilation Skin-friendly High absorption and emission of moisture 	

LINING

Heel pocket lining

 The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.

TOE PROTECTION CAP

Steel toe cap



- Protection against impacts of min. 200 joules and pressure loading of min.
 15 kN
- · Permanent edge coverage for cushioning
- Ergonomically shaped
- · Comfortable toe room
- Good coverage of the little toe area

INLAY SOLE

Full-length inlay sole SPORTIVE ESD



- ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.

PENETRATION RESISTANCE

Metal-free penetration protection

The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees.

The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.



OUTSOLE

MAXXIMO extended wedge double-density sole





- Excellent slip resistance
- Antistatic

Outsole: TPU (thermoplastic polyurethane)

• Colour: blue

• Profile depth: 3.5 mm

• Particularly abrasion-resistant

• Heat-resistant to approx. 130°C

• Flexible at cold temperatures to approx. -30°C

• Oil and fuel resistant

Midsole: PU (polyurethane) with a core made of Infinergy® by BASF

- The soft PU core provides a good impact absorption and high wearing comfort
- The core made of Infinergy® provides a very good cushioning with rebound effect

